

Ali-Deck SUPA JOIST

Specification Datasheet

The Ali-Deck Supa-Joist is an integral part of the Ali-Deck System! This clever extrusion is designed to act as both a support post and big span joist.

The connection plates allow for super fast installation and can be adjusted to suit most applications and conditions. It has also been designed to be connected together to give additional strength for applications where larger spans are required.





Benefits include:

- Increased span capabilities against timber or composite
- Increased spans by over 300%
- All aluminium
- Quick and easy to install
- Low maintenance
- Recyclable
- Stable in all weather conditions



Decking Joist Spans

DOMESTIC Joist Component Disposition

STANDARD SPECIFICATION 1/350 FIRM SPECIFICATION 1/480

CENTRE LINE OF JOIST

| LOAD 1.5kN SQM | | 600 | 1000 | 1200 | 1500 | 2000 |
|--------------------------------|---|------|------|------|------|------|
| JOIST SPANS - BETWEEN SUPPORTS | | | | | | |
| SINGLE JOIST | STANDARD specification: FIRM specification: | 3600 | 3100 | 3000 | 2700 | 2500 |
| SINGLE JOIST | | 3200 | 2800 | 2700 | 2500 | 2300 |
| DOUBLE JOIST | STANDARD specification: FIRM specification: | 5000 | 4200 | 4000 | 3800 | 3400 |
| DOUBLE JOIST | | 4500 | 3800 | 3600 | 3400 | 3100 |

COMMERCIAL Joist Component Disposition

STANDARD SPECIFICATION 1/350 FIRM SPECIFICATION 1/480 LOAD 4 0km SOM

CENTRE LINE OF JOIST

| FIRM SPECIFICATION 1/480 LOAD 4.0kN SQM | | 600 | 1000 | 1200 | 1500 | 2000 |
|--|---|------|------|------|------|------|
| JOIST SPANS - BETWEEN SUPPORTS | | | | | | |
| SINGLE JOIST | STANDARD specification: FIRM specification: | 2600 | 2300 | 2200 | 2000 | 1800 |
| SINGLE JOIST | | 2400 | 2100 | 2000 | 1800 | 1700 |
| DOUBLE JOIST | STANDARD specification: FIRM specification: | 3600 | 3100 | 3000 | 2800 | 2500 |
| DOUBLE JOIST | | 3300 | 2800 | 2700 | 2500 | 2300 |

Colour Options

The Supa Joists are available in two colours as shown to the right; textured silver grey and textured sand. Other colours are available on request.

The joists can be supplied without a powder coated finish to achieve the A1 fire rating and would therefore be a natural aluminium colour and appearance.





Warranty

The Supa Joist is supplied with a **30 year** warranty against splitting, cracking, warping, splintering, rotting, twisting and material or manufacturing defects. It has a minimum **60 year life** expectancy.



INCREASED SPAN
CAPABILITIES AGAINST
TIMBER OR COMPOSITE
OPTIONS BY OVER 300%



ALL ALUMINIUM



QUICK AND EASY TO INSTALL



COLOUR MATCHED TO THE DECK BOARDS



LOW MAINTENANCE



RECYCLABLE



STABLE IN ALL WEATHER CONDITIONS



Tel: 01622 235 672 Email: info@alideck.co.uk www.alideck.co.uk

